

545, 135

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 April 2005 (21.04.2005)


PCT

(10) International Publication Number  
**WO 2005/035133 A1**

- (51) International Patent Classification<sup>7</sup>: **B03C 3/155** (74) Agent: BUSHNELL, Robert, E.; Robert E. Bushnell & Law Firm, Suite 300, 1522 K Street, N.W., Washington, DC 20005-1202 (US).
- (21) International Application Number: PCT/US2003/037086
- (22) International Filing Date: 11 December 2003 (11.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/437,140 10 February 2003 (10.02.2003) US  
60/465,277 25 April 2003 (25.04.2003) US  
10/618,457 14 July 2003 (14.07.2003) US
- (71) Applicant and  
(72) Inventor: JAISINGHANI, Rajan, A. [US/US]; 13511 East Boundary Road, Suite D/E, Midlothian, VA 23112-3941 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: LOW PRESSURE DROP DEEP ELECTRICALLY ENHANCED FILTER



(57) Abstract: A method and apparatus using deep pleated filters (1) to provide efficient and safe electrically enhanced filtering (EEF), with ultra low pressure drop, higher efficiency of particulate removal and higher dirt holding capacity over the life of the filter (1). An EEF may be constructed with a housing (24), with or without an internal air moving device such as a fan, a deeply pleated filter (1), preferably a V-pack filter (31) with sets of downstream ground electrodes (4) and charge transfer electrodes (5) borne by the exterior surface of the filter packs (31) that form the filtering element

WO 2005/035133 A1



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*